



1. 电镀：镀金符合 MIL-G-45204(0.5u min)over(2u min) electroless Ni.
2. 阻抗：50 ohm
3. 所有的尺寸是毫米，D1公差为+0/-0.08

玻璃绝缘子型号	D1	D2	L1	L2	L3
G 201430 -4.4/1.5	2.0	0.3	1.4	1.5	1.5
G 201430 -8/4.6	2.0	0.3	1.4	2	4.6
G 201630 -3.9/0.4	2.0	0.3	1.6	1.9	0.4
G 201630 -8/4.6	2.0	0.3	1.6	1.8	4.6
G 251638 -8/4.6	2.5	0.38	1.6	1.8	4.6
G 251638 -12/2	2.5	0.38	1.6	8.4	2
G 252038 -9/2	2.5	0.38	2	5	2
G 253038 -12/2.2	2.5	0.38	3	6.8	2.2
G 281645 -5.2/1.1	2.8	0.45	1.6	2.5	1.1
G 281645 -8/4.6	2.8	0.45	1.6	1.8	4.6
G 281645 -12/3	2.8	0.45	1.6	7.4	3
G 301650 -7.8/2	3.0	0.5	1.6	4.2	2
G 301650 -12/5	3.0	0.5	1.6	5.4	5
G 302050 -6/1.5	3.0	0.5	2	2.5	1.5
G 302050 -6.5/2.2	3.0	0.5	2	2.3	2.2
G 302050 -8.5/2.2	3.0	0.5	2	4.3	2.2
G 302050 -12/4	3.0	0.5	2	6	4
G 302050 -12/5	3.0	0.5	2	5	5
G 303050 -14/4	3.0	0.5	3	7	4
G 304250 -9/2.2	3.0	0.5	4.2	2.6	2.2
G 304750 -9.4/2.2	3.0	0.5	4.7	2.5	2.2
G 304750 -12/2.2	3.0	0.5	4.7	5.1	2.2
G 472080 -6.5/2	4.7	0.8	2	2.5	2
G 553090 -9/3	5.5	0.9	3	3	3