



1. 电镀：镀金符合 MIL-G-45204(0.5u min)over (2u min) electroless Ni.
2. 所有的尺寸是毫米，D1公差为+0/-0.08

玻璃绝缘子型号	D1	D2	L1	L2	L3
DC 121645 -8/2.8	1.2	0.45	1.6	3.6	2.8
DC 161645 -12/3.4	1.6	0.45	1.6	7	3.4
DC 201650 -12/4.6	2.0	0.5	1.6	5.8	4.6
DC 201670 -11/4.6	2.0	0.7	1.6	4.8	4.6
DC 201670 -17/5	2.0	0.7	1.6	10.4	5
DC 201850 -14/6.1	2.0	0.5	1.8	6.1	6.1
DC 202060 -9/4	2.0	0.6	2	3	4
DC 203070 -11/4.6	2.0	0.7	3	3.4	4.6
DC 251670 -11/4.6	2.5	0.7	1.6	4.8	4.6
DC 251880 -12.8/5	2.5	0.8	1.8	6	5
DC 251880 -27/15	2.5	0.8	1.8	10.2	15
DC 252080 -25/13	2.5	0.8	2	10	13
DC 253070 -11/4	2.5	0.7	3	4	4
DC 2816100 -11.5/4.1	2.8	1.0	1.6	5.8	4.1
DC 2816100 -16/4.5	2.8	1.0	1.6	9.9	4.5
DC 2830100 -11.5/3	2.8	1.0	3	5.5	3
DC 2830100 -16/6.5	2.8	1.0	3	6.5	6.5
DC 303080 -25/3	3.0	0.8	3	19	3
接地端子	2.0	0.7	1.6	10.4	5