



Available Varirants

TYPE	"L"(mm)	IL. dB@max.		Marking	Weight(g)
		26.5GHz	40GHz		
SS540-29m29m-100	100	0.76	1.30	Tuyue YWWZZZ SS540-29m29m-100	12.2
SS540-29m29m-300	300	2.20	2.60	Tuyue YWWZZZ SS540-29m29m-300	16.7
SS540-29m29m-500	500	2.60	4.30	Tuyue YWWZZZ SS540-29m29m-500	21.0
SS540-29m29m-XXXX	XXXX			Tuyue YWWZZZ SS540-29m29m-XXXX	

XXXX is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

Assembly Parts

Connector left: 2.92mm-J405G
Connector right: 2.92mm-J405G
Cable: SS086

Electrical data

Impedance	50 Ω
Frequency	DC to 40GHz
VSWR	≤ 1.35 DC to 26.5GHz ≤ 1.44 DC to 40.0GHz
Insertion loss	See table available variants
RF-leakage	≥ 100 dB up to 1 GHz

Mechanical data

Minimum Bend Radius
Single: 12.5 mm
Multiple: 38.1 mm
Jacket Diameter: 2.64mm

Environmental data

Temperature range	-55°C to +125°C
2002/95/EC (RoHS)	compliant