




Available Varirants

TYPE	"L"(mm)	IL. dB@max 18GHz	Marking	Weight(g)
BLU18E-NmSm-500	500	0.89	Tuyue YWWZZZ BLU18E-NmSm-500	80
BLU18E-NmSm-1000	1000	1.58	Tuyue YWWZZZ BLU18E-NmSm-1000	116
BLU18E-NmSm-2000	2000	2.97	Tuyue YWWZZZ BLU18E-NmSm-2000	188
BLU18E-NmSm-XXXX	XXXX		Tuyue YWWZZZ BLU18E-NmSm-XXXX	

XXXX is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

Assembly Parts

Connector left: N-J210EG
Connector right: SMA-J210EG
Cable:210E

Electrical data

Impedance	50 Ω
Frequency	DC to 18GHz
VSWR	≤ 1.30 DC to 18GHz
Insertion loss	See table available variants
RF-leakage	≥ 100 dB up to 1 GHz

Mechanical data

Minimum Bend Radius
Single: 12.5 mm
Multiple: 38.1 mm
Jacket Diameter: 5.5 mm

Environmental data

Temperature range	-40°C to +85°C
2002/95/EC (RoHS)	compliant