



#### Available Variants

TYPE	"L"(mm)	IL. dB@max.		Marking	Weight(g)
		3GHz	6GHz		
LIM13-DmDm-1000	1000	0.59	0.86	Tuyue YWWZZZ LIM13-DmDm-1000	291
LIM13-DmDm-1500	1500	0.89	1.29	Tuyue YWWZZZ LIM13-DmDm-1500	363
LIM13-DmDm-2000	2000	1.05	1.60	Tuyue YWWZZZ LIM13-DmDm-2000	436
LIM13-DmDm-XXXX	XXXX			Tuyue YWWZZZ LIM13-DmDm-XXXX	

**XXXX** is cable length and we can follow customer demand. Y - year; ww - Week; zzz - Serial No. .

#### Assembly Parts

Connector left: 7/16-JB5  
Connector right: 7/16-JB5  
Cable: LIM250

#### Electrical data

Impedance	50 Ω
Frequency	DC to 6 GHz
VSWR	≤1.30, DC to 6GHz
Insertion loss	See table available variants
PIM	≤-165 dBc
RF-leakage	≥ 90 dB up to 1 GHz

#### Mechanical data

Minimum Bend Radius  
Single: 45 mm  
Multiple: 100 mm  
Jacket Diameter: 7.0 mm

#### Environmental data

Temperature range	-40°C to +85°C
2002/95/EC (RoHS)	compliant